



PRODUCT NUMBER: 2332242

Check & Go Amber PU 3

Handling sharp parts in a dry or greasy environment.

Honeywell

Overview

Reference Number

2332242

Product Type

Gloves

Range

Cut and Puncture Protection

Line

Cut resistant

Brand

Honeywell

Industry

- Automotive and Part Manufacturer
- Aviation
- Building and Construction
- Catering
- Energy or Electricity
- Glass Industries
- Logistics
- Maintenance
- Metal steel
- Paper Industries
- Services
- Telecoms
- Transportation
- Utilities

Product Use

Handling sharp parts in a dry or greasy environment.

Helps to provide safety managers with visual recognition of the cut protection level

Features & Benefits

Feature

White HPPE/lycra® / Polyamide knitted glove
Amber polyurethane coating on palm and tips of fingers

Benefit

COMFORT

The knitting technique helps to obtain a glove that conforms snugly to the hand, with good dexterity.
The glove offers maximum comfort and added sturdiness.
The cool HPPE touch gives an added sensation of comfort.
The tight knit (gauge 13) gives the glove perfect support, limits the penetration of dirt and offers a good touch.
The glove's ventilated back optimises its breathability.

RESISTANCE

The HPPE/lycra® thread provides outstanding properties against cuts.
 The polyurethane coating at the palm and fingertips provides outstanding abrasion resistance.
 Caution! Do not expose this glove to the heat.

SAFETY

Color coding on top of the hand and coating color helps safety manager and workers to visually recognize the level of cut protection.

Technical Description

Description

CE CATEGORY : II Intermediary risks
 In accordance with standards :
 EN 420-2003 EEC Basic standards
 EN 388-2003 Mechanical hazards

CHARACTERISTICS :

White HPPE/lycra®/polyamide knitted glove
 Amber polyurethane coating on the palm and fingertips

Product Technology

Knitted Coated

Fiber

HPPE polyamide and lycra®

Gauge

13

Glove/liner color

White

Coating Type

Polyurethane

Coating Color

Amber

Length

25 cm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

Sizes

7 to 11

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance (Coupe test)	3
Tear resistance	4
Puncture resistance	2

Packaging Label

Tagging

CE HONEYWELL
 2332242 XX
 EN 420
 EN 388 : 4342

Certifications

 E.C. Declaration of Conformity

EC Category PPE

2


Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0075/797/162/01/12/0055 EXT 03/04/2013

EC Attestation

 AET 2332242 Update 02

EC Attestation Number

0075/797/162/01/12/0055 EXT 03/04/2013

Additional Information

User Manual

UI 102

User Information Sheet

102

Maintenance

Storage Information

Minimum packaging 10 pairs.

Cartons of 100 pairs.

Care Instructions

This article can be cleaned at 40°C without risk of damaging the mechanical performances.